

# FIX-A-LOO



1 YEAR WARRANTY

This warranty runs for one year from the date of purchase.

Our products come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other loss or damage. You are also entitled to have the goods repaired if the goods fail to be of an acceptable quality and the failure does not amount to a major failure.

#### What is covered:

This warranty covers the product for domestic use only. The warranty covers any defects in materials or workmanship with the exception of the reasons stated below.

#### What is not covered:

This warranty does not cover wear and tear to working parts, misuse or abuse. It does not cover discolourations due to exposure or cleaning chemicals.

#### Claim procedure:

If you believe you have a legitimate claim, please contact FIX-A-TAP Australia via our website at [www.fixatap.com.au/warranty](http://www.fixatap.com.au/warranty) to complete the warranty claim form. Alternatively you can contact our office on 02 9476 7400.

#### Any written correspondence should be sent to:

FIX-A-TAP Australia Pty Ltd,  
PO Box 200,  
Wahroonga NSW 2076

Please keep your receipt for proof of purchase.

PLUMBCONNECT  
PLUMBERS REGISTRY

#### Need a plumber?

To find a plumber in your area, consult our PlumbConnect Registry using the QR code or via our website:

[www.fixatap.com.au/find-a-plumber](http://www.fixatap.com.au/find-a-plumber)



**FIX-A-TAP® AUSTRALIA PTY LTD**  
The Ultimate Plumbing Solution  
PO Box 200 Wahroonga NSW 2076  
[www.fixatap.com.au](http://www.fixatap.com.au)  
Made in China  
© 2021 FIX-A-TAP



A family  
owned  
Australian  
business

Quality Assured Products  
FIX-A-TAP has been providing Australians  
with quality plumbing products since 1972.

# ECONIX TOILET SEAT

CODE: 253224

## INSTALLATION INSTRUCTIONS



1. Open the hinge cavities by unclipping the top covers to flip open (away from the seat).
2. Insert the bolts into the hinge cavities to fit into the depressed circles.



3. Fit the bolts through the pan holes, and align the toilet seat with the pan.
4. Firmly close the top covers of the hinge cavities.



5. Add the washers and nuts to the bolts on the underside of the pan and fasten securely.

## CLEANING INSTRUCTIONS

Clean with water or a gentle household detergent. Do not apply bleach or a harsh chemical based cleaner.