

TRADESMEN TAP RESEATER

EASY INSTALLATION

1. Turn off water at mains.
2. Remove tap assembly from body of tap & remove tap valve.
3. Insert tap reseater into tap body and secure by screwing into tap thread.
4. Ensure correct depth by unscrewing centre threaded spindle so as cutting blade meets seat but is still able to move freely.
5. Carefully reseal by turning T-bar in clockwise motion with slight hand pressure.
6. To increase the depth of the cut, turn centre threaded spindle 1/8 of a turn clockwise.
7. Remove tap reseater and inspect tap seat.
8. Repeat steps 5 and 6 as necessary.
9. Replace tap assembly, turn on water and check for leaks.

HANDY HINT

If seat is damaged beyond repair, fit new
FIX-A-TAP Stainless Steel Seat (Product #229007 or #222329).



A family
owned
Australian
business

Quality Assured Products

FIX-A-TAP has been providing
Australians with quality plumbing
products since 1972.



ari.org.au

FIX-A-TAP®

AUSTRALIA PTY LTD

The Ultimate Plumbing Solution.

PO Box 200 Wahroonga

NSW 2076 Australia

Made in China ©2023

www.fixatap.com.au

Visit our website for socials,
plumbers, product info & more



9 312232 2094 12 >