

# BOSTON®

GREAT VALUE SOLUTIONS

\$\$

## LIQUID SEALANT



Approved by the  
Aust. Gas Assoc.  
(Cert. No. 7583  
Class III - 2000kPA).

Temp. Range: -10°C  
to +135°C (Gas).  
Up to 55°C (Water).



Type Tested

AS/NZS 4020  
PTT40067  
SAI GLOBAL



[arl.org.au](http://arl.org.au)

### ANAEROBIC SEALANT FOR GAS & WATER PIPE METAL THREADS

## **LIQUID SEALANT IS SUITABLE FOR GAS & WATER**

**APPLICATION:** Remove oil contamination from the area where the sealant is to be applied. Apply sealant to one surface, covering 2-3 thread rotations and connect threads. Excess sealant must be wiped off. Curing time is 10-20 minutes, however full cure time is 24 hours. Hand tools required for disassembly.

**IMPORTANT:** Anaerobic sealant seals through lack of oxygen. 50g sealant enclosed, packaging is larger to prevent in-bottle curing. Sealant exposed to air will not cure. Metal to metal use only. Not suitable for plastic, glass or rubber. Excess sealant must be wiped off to prevent a metallic taste from uncured sealant. Not recommended for continuous steam temperatures above 135°C. Apply this product with good ventilation. If product comes into contact with eyes or skin, flush with clean water immediately. Store in a cool, dry area. Keep away from children.

**Net: 50g**

**FIX-A-TAP®**

Australia Pty Ltd

PO Box 200

Wahroonga

NSW 2076

fixatap.com.au

Made in China



9 312232 260963 >